

## CLEVERTRONICS UPS WEATHERPROOF EXIT



## PRODUCT INFORMATION

Part Number	LWELED-UPS
Description	Weatherproof Emergency EXIT. Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others)
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained with no integral battery backup (UPS)
Testing System	N/A - Manual test switch
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts
IP Rating	IP66/IP67
Operating Temperature	-25°C to 40°C
AS2293 Classification	C <sub>0</sub> =E2 C <sub>90</sub> =E2
Impact Rating	IK10
Viewing Distance	24m

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8002331	PCA:LCFLED Driver.UPS #CT10164-L4
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D2

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*

## IMPORTANT NOTICE:

If there are separate supply cables coming to the fitting the contractor must install an additional, external changer over relay to facilitate the changeover from the 240V AC cables to the backup 240V AC cables. The fitting only has the capacity to accept one supply input.