



LWELED-WM

CLEVERTRONICS L10 WEATHERPROOF WALL MOUNT EXIT



PRODUCT INFORMATION	
Part Number	LWELED-WM
MIC	AUA01320130001
Description	L10 Optimum Wall Mounted IP66/67 Weatherproof EXIT, Enabled with Clevertest Plus
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 130mm x 190mm
Weight	2.7kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x High Intensity, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.8 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK08 (side surface) IK09 (front surface)
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=E1.6 C90=E1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
AUM01370350001	LWELED-CKIT-50, WP LED Exit, Control Kit, L10, OWC, CTP, 50mA
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D4

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.