



## CWELED-DALI-BLK

### CLEVERTRONICS LP WEATHERPROOF EMERGENCY EXIT



#### PRODUCT INFORMATION

Part Number	CWELED-DALI-BLK
MIC	AUA02220080003
Description	LP Premium weatherproof Emergency Exit, Black
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Ceiling or Wall Mount
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.0 Watts (Max)
Inrush Current (Max)	51A
Earth Leakage	0.333mA
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D4, C90=E3.2
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

#### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	Emergency LED Panel
8002329	Emergency Driver
8003060	Emergency Node – DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.