



## LJWELED-40

### CLEVERTRONICS L10 JUMBO WEATHERPROOF UNIVERSAL EXIT



#### PRODUCT INFORMATION

Part Number	LJWELED-40
MIC	AUA01320240001
Description	L10 Optimum Jumbo Weatherproof Universal Exit, Enabled with Clevertest Plus
Construction	Polycarbonate
Mounting	Wall mount, Single-sided Ceiling mount, Single & Double-sided
Dimensions L x W x H	570mm x 117mm x 340mm
Weight	5.6kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included
Lamp(s)	12 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.9 Watts (Standby), 4.8 Watts (Max)
IP Rating	IP66
IK Rating	IK09
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E4
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

#### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	BATT:L10 3.3V 2.5AH 200mm lead, no BRKT
8050640	LED: HWSUB: CT10758-D1
AUM01370050001 LJELED-40-CKIT-110	DRIVER: Jumbo LED Exit, Control Kit, L10, 110mA

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.