




CWELED-A-DALI

LP Premium weatherproof Emergency EXIT with acrylic cover



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | CWELED-A-DALI |
| MIC | AUA02220060102 |
| Description | LP Premium weatherproof Emergency EXIT with acrylic cover |
| Construction | Polycarbonate clear cover, glass reinforced nylon PA66 base |
| Mounting | Wall, ceiling single-sided & ceiling double-sided |
| Dimensions L x W x H | 410mm x 272mm x 100mm |
| Cut-Out | N/A |
| Weight | 3.4kg |
| Operating Mode | Maintained |
| Testing System | DALI Registered |
| Battery | Battery Lithium Iron Phosphate, 3.2V 1100mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x LED lamp bar assembly 100,000 hours, LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=12Y/00M) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8W/4W (STANDBY/MAX) |
| Inrush Current (Max) | 15A, 260µs |
| Earth Leakage | 0.333mA |
| IP Rating | IP66/67 |
| IK Rating | IK04 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C0=E4, C90=E2.5 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) |  |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1550105 | Battery |
| 8002710 | LED Strip |
| 8003060 | DALI Node |
| 8002329 | Driver Pack |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.