



DYGC-CP-SND-NC-RL-HV

CleverEvac Dynamic Green Exit, Surface Mount, LP, Normally Closed, Sounder, Zoneworks XT Hive, Running Man Arrow Left, Single Sided



Dynamic LEDs Sequencing Arrow & Sounder Activated

PRODUCT INFORMATION

Part Number	DYGC-CP-SND-NC-RL
MIC	AUA02850310001
Description	CleverEvac Dynamic Green Exit, Surface Mount, LP, Normally Closed, Sounder, Zoneworks XT Hive, Running Man Arrow Left, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	446mm x 214mm x 72mm
Weight	2.4kg
Operating Mode	Maintained – Sequencing arrows & Sounder activated on opening of the VF/24V contact and capable of being activated in power-on and battery-backed mode
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3200mAh Nickel Cadmium, 3.6V 600mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Two elements (Running Man and Arrow Left)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4.0 Watts (Standby), 10 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.25, C90=C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8003025	EM LED
8002927	EM Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order