



## DYGL-UP-DS-RAOW-HV

CleverEvac Dynamic Green Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow One Way, Double Sided



PRODUCT INFORMATION	
Part Number	DYGL-UP-DS-RAOW-HV
MIC	AUA01850110001
Description	CleverEvac Dynamic Green Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with Acrylic diffuser
Mounting	Recessed, Double-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Operating Mode	Maintained - Sequencing arrows (green LEDs) activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. <b>Dynamic GREEN default set to activate upon mains power fail</b>
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Double sided Pictograph, two elements (Running Man with Arrow)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5; C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	Battery
AUM01870340001 DYGL-UP-CKIT-HV	Emergency Driver
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order