




## DYGC-UP-WM-RR

CleverEvac Dynamic Green Exit, Wall Mount, LP, Running Man Arrow Right, Single Sided



### PRODUCT INFORMATION

Part Number	DYGC-UP-WM-RR
MIC	AUA00000001101
Description	CleverEvac Dynamic Green Exit, Wall Mount, LP, Running Man Arrow Right, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained – Sequencing Inward Green LEDs Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Manual
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Right)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.8W (Standby), 4.7W (Max)
Inrush Current (Max)	15.9A @ 140µs
Earth Leakage	0.326mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=C8, C90=C32, C180=E4, C270=C32
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



## DYGC-UP-WM-RR

CleverEvac Dynamic Green Exit, Wall Mount, LP, Running Man  
Arrow Right, Single Sided

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8003325	LED strip
AUM02570020001 DYGC-UP-CKIT	EM Driver Pack

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.