



DYRL-UP-CM-RR-HV

CleverEvac Dynamic Red X Exit, Ceiling Mount,
L10 Nanophosphate, Zoneworks XT Hive,
Running Man Arrow Right, Single Sided



PRODUCT INFORMATION

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Part Number | DYRL-UP-CM-RR-HV |
| MIC | AUA00000006001 |
| Description | L10 Optimum CleverEVAC Dynamic Green & Red X Blade Exit Sign, with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green & Red X Enhancement. Dynamic Green Default Set to Activate Upon Mains Power Fail. |
| Construction | PC/ABS Body with PC Diffuser and Metal Enclosure |
| Mounting | Ceiling Mount, Single-sided |
| Dimensions L x W x H | 391mm x 90mm x 257mm |
| Weight | 5.9 kg |
| Operating Mode | Maintained Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's. Activated Over the XT HIVE Network or on VF/24V Input Trigger. Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail. |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Single-sided Pictograph, Two Elements (Running Man with Arrow Right) |
| Lamp(s) | LED Panel, 100,000 hours |
| Operating Voltage | 220-240V AC; 50Hz |
| Power Consumption | 2.0W (Standby), 9.0W (Max) |
| Inrush Current (Max) | 15.9A @ 140µs |
| Earth Leakage | 0.295mA |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0: D5, C90: C25, C270: C25, C180: E6.3 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-----------------------------------|-----------------------|
| 1530250 | Battery |
| AUM01870350001 DYRL-UP-CKIT-HV | Emergency Driver Pack |
| 8003191 | Node - HIVE |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.