



## DYRL-UP-CM-RL

CleverEvac Dynamic Red X Exit, Ceiling Mount, L10 Nanophosphate, Running Man Arrow Left, Single Sided



### PRODUCT INFORMATION

Part Number	DYRL-UP-CM-RL
MIC	AUA01550220001
Description	CleverEvac Dynamic Red X Exit, Ceiling Mount, L10 Nanophosphate, Running Man Arrow Left, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Ceiling Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained – Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Manual
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Left)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.7W (Standby), 8.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5, C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530250	Battery
AUM01570070001 DYRL-UP-CKIT	Emergency Driver Pack

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.