




DYRC-UP-R

CLEVEREVAC DYNAMIC GREEN & RED X BLADE EXIT SIGN



PRODUCT INFORMATION	
Part Number	DYRC-UP-R
MIC	AUA02550290001
Description	LP Premium CleverEVAC Dynamic Green and Red X Blade EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail.
Construction	PC/ABS body with Acrylic diffuser
Mounting	Recessed, Single-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail.
Testing System	Manual
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.7 Watts (Standby), 8.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5 C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550250	Battery
AUM02370420001	Emergency Driver Pack
8050440	Emergency LED Strip
8050450	Emergency LED Strip

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.