



DYRL-UP-CM-RL-HV

CleverEvac Dynamic Red X Exit, Ceiling Mount,
L10 Nanophosphate, Zoneworks XT Hive,
Running Man Arrow Right, Single Sided



PRODUCT INFORMATION	
Part Number	DYRL-UP-CM-RL-HV
MIC	AUA0000005901
Description	CleverEvac Dynamic Red X Exit, Ceiling Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow Left, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Ceiling Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's. Activated Over the XT HIVE Network or on VF/24V Input Trigger. Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Right)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.1W (Standby), 5.0W (Max)
Inrush Current (Max)	15.9A @ 140µs
Earth Leakage	TBD
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D5, C90, C270 : C25, C180=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530250	Battery
AUM01870350001 DYRL-UP-CKIT-HV	Emergency Driver Pack
8003191	Node - HIVE

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.