




LVP2LED-M-P

Argonaut Vandal Resistant 600mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, Clevertest Plus



PRODUCT INFORMATION

Part Number	LVP2LED-M-P
MIC	AUB01330020003
Description	L10 Optimum 600mm Argonaut LED Vandal Batten with Battery POD
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	790mm x 140mm (Batten) x 120mm (POD width 136mm)
Weight	3.2kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LC 50W 350-1050mA
Lamp(s)	1 x LED module, 4000K natural white, 100,000h [L80/ B20, Ta 40°C], CRI Ra>80
LED MacAdam Step (SDCM)	3
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	0.9W/21.4W/25.2W (STDBY OFF/STDBY ON/ MAX)
Inrush Current (Max)	22.4A
Earth Leakage	0.354mA
Total Lumen Output	2529lm @109lm/W (based on non-emergency version @23W)
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
AS2293 Classification	C0=D100 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	Battery
8002754	LED Assembly
AUM01370610001 LCPLED-4W-CKIT-HBL	Emergency Driver
1330055	240V Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order