

CLEVERTRONICS L10 HIGH IMPACT SECURITY CEILING MOUNT



Tamperproof screws

PRODUCT INFORMATION

Part Number	LVELED-CM-DALI
MIC	AUA01230010102
Description	L10 Lithium Nanophosphate Cleverfit PRO Exit in vandal resistant case, ceiling mounted, supports 4 hour emergency duration
Construction	Strong steel body with PC diffusers
Mounting	Single or Double Side Ceiling Mount
Dimensions L x W x H	425mm x 100mm x 270mm
Weight	6.6kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D3.2 C ₉₀ =E8
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002550	PCA:CCFPRO Driver No Sw.A. #CT10270-L1
8002250	PCA:CPRO LED Board w Loom. #CT10172-A1.
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

