



CUBPRO-SM-TH-DALI-DS-RAOW

CLEVERTRONICS LP ULTRABLADE PRO SURFACE MOUNT,
DOUBLE SIDED, THEATRE



PRODUCT INFORMATION

Part Number	CUBPRO-SM-TH-DALI-DS-RAOW
MIC	AUA02260440002
Description	LP Premium wall mounted IP66/67 weatherproof Exit, Theatre Mask, Enabled with Clevertest Plus
Construction	Base material: Polycarbonate Diffuser cover material: Polycarbonate
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 190mm x 130mm
Cut-Out	N/A
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man with Arrow One Way
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.7W(standby), 4.0W (max)
Inrush Current (Max)	N/A
Earth Leakage	N/A
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002178	LED
8003173	Emergency Driver
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.