



CCFLED-TH-DS-R

Cleverfit Exit, Surface Mount, LP, Clevertest Plus, Theatre Version, Running Man, Double Sided



PRODUCT INFORMATION

Part Number	CCFLED-TH-DS-R
MIC	AUA02360300001
Description	Cleverfit Exit, Surface Mount, LP, Clevertest Plus, Theatre Version, Running Man, Double Sided
Construction	ABS Body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall, Ceiling Single-sided & Ceiling Double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not Activated by Default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask with Double-sided Running Man
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5W (Standby), 3.7W (Max)
Inrush Current (Max)	15A, 260µs
Earth Leakage	0.333mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002348	Driver
8002710	LED Strip