



LUBPRO-SM-RS-TH-R

CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT
SURFACE MOUNTED – THEATRE VERSION - ROD SUSPENDED



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-RS-TH-R
MIC	AUA01360240001
Description	L10 Optimum Ultrablade Pro Blade Exit, Surface Mounted, Rod suspended, Theatre Version, Enabled with Clevertest Plus
Construction	PC/ABS body with PC Diffuser
Mounting	Surface Mount Ceiling - Rod suspended Blade suspended with 5mm diameter; steel rods secured by 2 x “grub-screw” at each end of the rod. Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Note: Steel Rods supplied with fitting assembly, 1500mm long.
Dimensions L x W x H	Blade Assembly 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 360mm x 47mm x 72mm
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Single Sided, Running Man
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4W (Standby), 3.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8011493	LED Strip
8003135	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order