



LUBPRO-SM-TH-HV-DS-R

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive, Theatre Version, Running Man, Double Sided



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-TH-HV-DS-R
MIC	AUA01860430001
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man, Double Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Surface Mounted, Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Running Man Arrow One Way, Double Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002178	LED Strip
8003135	Driver
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order