

CLEVERTRONICS L10 CLEVERFIT EXIT, THEATRE DOUBLE SIDED



PRODUCT INFORMATION

Catalogue Number	LCFLED-TH-DS-R
Description	L10 Optimum Cleverfit Emergency Exit, Theatre Mask, Double Sided, No Arrow
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper proof Cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Clevertest Plus
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask with double sided Running man (must specify diffuser combination)
Lamp(s)	6 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.7 Watts during first 16hr charge
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBRKT
8002330	PCA:LCFLED Driver. #CT10164-L4.
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1

