



LCFLED-TH-RL

Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Left, Single Sided



PRODUCT INFORMATION

Part Number	LCFLED-TH-RL
MIC	AUA01360200002
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Left, Single Sided
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper Proof Cover
Mounting	Wall or Ceiling, Single-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Testing System	Clevertest Plus Enabled (Not activated by default)
Operating Mode	Maintained
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man, Single Sided
Lamp(s)	6 x High Intensity LED, Surface Mounted onto replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	1.8 Watts (Standby), 3.2 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8002301	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.