



LUBPRO-RS-TH-HV-RR

CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT
RECESSED - ROD SUSPENDED



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | LUBPRO-RS-TH-HV-RR |
| MIC | AUA01860420002 |
| Description | L10 Optimum Ultrablade Pro Blade Exit, Rod suspended |
| Construction | PC/ABS body with PC Diffuser |
| Mounting | Recessed Ceiling - Rod suspended Blade suspended with 5mm diameter; steel rods secured by 2 x "grub-screw" at each end of the rod. Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Note: Steel Rods supplied with fitting assembly, 1500mm long. |
| Dimensions L x W x H | Blade Assembly: 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 347mm x 48mm x 65mm Ceiling Mount Cover Plate: 385mm x 67mm |
| Cut-Out | 350mm x 48mm |
| Minimum Depth | 80mm |
| Weight | 1.5kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery | Lithium Nanophosphate 3.3V 2.5Ah |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | Theatre Version, Running Man Arrow Right, Single Sided |
| Lamp(s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8W (Standby), 4.2W (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | N/A |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|----------------------------------|-------------|
| 1530050 | Battery |
| 8011493 | LED Strip |
| AUM01870040002 LUBPRO-CKIT-HV | Driver Pack |
| 8003191 | HIVE Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order