



CUBPRO-SM-TH-RL

CLEVERTRONICS LP ULTRABLADE PRO SURFACE MOUNT EXIT, THEATRE



PRODUCT INFORMATION	
Part Number	CUBPRO-SM-TH-RL
MIC	AUA02360260002
Description	LP Premium Ultrablade Pro Surface Mount Blade Exit, Single Sided, Theatre
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling Mounted
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man, Arrow Left
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8003135	Driver
8002178	Emergency LED Panel

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.