



## LCFPRO-TH-DS-RAOW

CLEVERTRONICS L10 CLEVERFIT PRO EXIT, THEATRE MASK



### PRODUCT INFORMATION

Part Number	LCFPRO-TH-DS-RAOW
MIC	AUA01360020001
Description	L10 Optimum Cleverfit Pro Emergency Exit, Theatre Mask, Enabled with Clevertest Plus
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, ceiling mount, double sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Running Man Arrow One Way, Double Sided (Must specify diffuser combination)
Lamp(s)	6 x LED, 100,000
Operating Voltage	240V AC: 50Hz
Power Consumption	2.5 Watts (Standby), 3.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002710	Emergency LED Panel
8003154	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.