



CCFLED-TH-HV-RL

CLEVERTRONICS LP CLEVERFIT EXIT - THEATRE



PRODUCT INFORMATION

Part Number	CCFLED-TH-HV-RL
MIC	AUA02860200001
Description	LP Premium Cleverfit Emergency Exit, Theatre Mask
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man, Arrow left, Single Sided
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	n/a
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002348	Driver
8002710	Emergency LED Panel
8003191	Emergency Node – HIVE (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order