



## LCFPRO-TH-HV-RR

CLEVERTRONICS L10 CLEVERFIT PRO EXIT THEATRE



### PRODUCT INFORMATION

Part Number	LCFPRO-TH-HV-RR
MIC	AUA01860060001
Description	L10 Optimum Cleverfit Pro Emergency Exit, Theatre Mask
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, ceiling and single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, running man with right arrow, single sided (must specify diffuser combination)
Lamp(s)	6 x LED, 100,000
Operating Voltage	200-240V AC; 50Hz
Power Consumption	2.5 Watts (Standby) 3.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8002710	PCA: Duris LED Strip Cleverfit Pro CT10276-D3
1530030	BATT:L10 3.3V 2.5AH 260mm lead, no BRKT
8003156	PCA:CCF-Pro #CT10622 6C20 DALI REG
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.