

CLEVERTRONICS LP WEATHERPROOF EXIT, THEATRE



PRODUCT INFORMATION

Part Number	CWELED-TH-RL
Description	LP Premium weatherproof Emergency EXIT, Theatre, Enabled with Clevertest Plus
Construction	Polycarbonate clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man left (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 5.1 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Impact Rating	IK10
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550190	BATT:LP 3.2V 1500mAh 390mm lead, noBRKT.
8002325	PCA:CCFLED Driver. #CT10164-L4
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1

