

CLEVERTRONICS ECONOMY LITHIUM CLEVERFIT EXIT, THEATRE



PRODUCT INFORMATION

Part Number	ECFLED-LI-TH-DS-RAOW
Description	Economy Lithium Cleverfit Emergency Exit, Theatre Mask
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.2kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask with double sided Running man, Arrows (right arrow one side left arrow the other side)
Lamp(s)	4 x LED, 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.1 Watts (Standby), 2.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560200	BATT:EcoLith 3.2V 1.1Ah 210mm lead,noBKT
8002900	PCA:LED Strip ECFLED-LI CT10242-D1
8002880	PCA:Driver ECOLITH Cleverfit CT10240-L4

