

CLEVERTRONICS L10 ULTRABLADE PRO, THEATRE



PRODUCT INFORMATION

Part Number	LUBPRO-TH-DALI-R
MIC	AUA01260610202
Description	L10 Lithium Nanophosphate Ultrablade Pro blade Exit, Theatre
Construction	ABS frame with acrylic & PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8002178	PCA:LL-Pro L10 2pinML 60mA #CT10142-L5
LUBPRO-CKIT	Ultrablade Pro,Control Only, L10
8003060	PCA: DALI Node #CT10629-Ax

