



## CCFLED-TH-DALI-DS-RAOW

CLEVERTRONICS LP CLEVERFIT EXIT, THEATRE



### PRODUCT INFORMATION

Part Number	CCFLED-TH-DALI-DS-RAOW
MIC	AUA02260020002
Description	LP Premium Cleverfit Emergency Exit, Theatre Mask
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8KG
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask with Double-sided Running Man, Arrows (Right Arrow One Side Left Arrow the Other Side)
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002329	Driver
8002710	Emergency LED Panel
8003060	Emergency Node - DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.