

CLEVERTRONICS LP ULTRABLADE PRO, THEATRE



PRODUCT INFORMATION

Part Number	CUBPRO-TH-DALI-R
MIC	AUA02260380202
Description	LP Premium Ultrablade Pro blade Exit, Theatre
Construction	PC/ABS body with PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550130	BATT:LP 3.2V 1500mAh 260mm lead,no BRKT.
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
CUBPRO-CKIT	Ultrablade Pro,Control Only, LP
8003060	PCA: DALI Node #CT10629-Ax

