



## LUBPRO-TH-RR

CLEVERTRONICS L10 ULTRABLADE PRO  
THEATER MASK



PRODUCT INFORMATION	
Part Number	LUBPRO-TH-RR
MIC	AUA01360100002
Description	L10 Ultrablade Pro Recessed Blade Exit with Theatre Mask, Enabled with Clevertest Plus
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Running Man, Arrow Right, Single Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.2 Watts (Max)
Inrush	13.08<84 $\mu$ s
Earth Leakage	0.331
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	Battery
8002178	Emergency LED Panel
AUM01370010002 LUBPRO-CKIT	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.