

CLEVERTRONICS ECONOMY LITHIUM CLEVERFIT EXIT, THEATRE



PRODUCT INFORMATION

Part Number	ECFLED-LI-TH-RL
Description	Economy Lithium Cleverfit Emergency Exit, Theatre Mask
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.2kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man left (Must specify diffuser combination)
Lamp(s)	4 x LED, 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.1 Watts (Standby), 2.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560200	BATT:EcoLith 3.2V 1.1Ah 210mm lead,noBKT
8002900	PCA:LED Strip ECFLED-LI CT10242-D1
8002880	PCA:Driver ECOLITH Cleverfit CT10240-L4

