



LCFLED-TH-HV-R

L10 Cleverfit Exit, Theatre
(Zoneworks XT HIVE)



PRODUCT INFORMATION

Part Number	LCFLED-TH-HV-R
MIC	AUA01860110002
Description	L10 Optimum LED Cleverfit Emergency Exit with Theatre Mask, Zoneworks XT HIVE
Construction	ABS Body and Diffuser with Clear Polycarbonate Tamper Proof Cover
Mounting	Wall or Ceiling Mounted, Single Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running Man, Single Sided
Lamp(s)	6 x LED, 100,000Hrs
Operating Voltage	220V-240V AC: 50Hz
Power Consumption	2.8 Watts (Standby), 4 Watts (Max)
Inrush Current (Max)	12.537A, 82µs
Earth Leakage	0.324mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002329	Driver
8002710	LED Strip
8003191	HV Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.