



LWP2LIFE-PRO-WPPOD-HV

Lifelight Pro IP65 Weatherproof Twin Pod Emergency,
Surface Mount, L10 Nanophosphate, Zoneworks XT Hive



PRODUCT INFORMATION

Part Number	LWP2LIFE-PRO-WPPOD-HV
MIC	AUT01820080001
Description	Lifelight Pro IP65 Weatherproof Twin Pod Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive
Construction	Polycarbonate
Mounting	Surface mount
Dimensions L x W x H	520mm x 180mm x 135mm
Weight	3.4kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 6.0 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	Ceiling Mount: C0=D160 C90=D160 Wall Mount: C0=D160 C90=D80 C270=D125
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY x 4
2750353	LED ASSEMBLY x 2
AUM01870090001 LLIFE-PRO-CKIT-HV-NP	EM DRIVER x 2
8003191	HIVE NODE

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order