

CLEVERTRONICS ECONOMY LITHIUM BOXLITE WALL MOUNT



PRODUCT INFORMATION

Part Number	EBLLED-WM-LI
Description	Economy Lithium Boxlite Exit wall mount
Construction	ABS body and PC diffuser
Mounting	Wall mount
Dimensions L x W x H	375mm x 105mm x 160mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 2.3 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E2 C ₉₀ =E2
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560200	BATT:EcoLith 3.2V 1.1Ah 210mm lead,noBKT
8002715	PCA:LED Strip EBLLED-LI CT10276-no shade
8002970	PCA: EBLLED-LI #CT10614-L1

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

