



CLEVERTRONICS L10 OPTIMUM RECESSED WALL MOUNT LED EXIT (DALI)



PRODUCT INFORMATION

Catalogue Number	LBLLED-REC-WM-DALI-R
Description	LED L10 OPTIMUM Recessed Wall Mounted Exit, 24 metre viewing Distance
Construction	Body: Folded sheet steel. Power coat – Dulux Pearl White Trim Finish: Standard: Stainless Steel. Power coat colours available. Specify when ordering.
Mounting	Recessed Wall
Dimensions L x W x D	350mm x 200mm (Trim) x 81mm (Wall depth)
Wall Cut-out LxWxD	325mm x 180mm x 81mm
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Charging Method	Intelligent current limited constant voltage charger
Diffuser	(must specify diffuser combination)
Lamp(s)	6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar - 100,000 hour
Operating Voltage	240V
Power Consumption	4.4W
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	N/A

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery: 3.3 Volt 2.5Ah Li-ion
8002430	PCA: Duris P5 6 LED Strip.L10, #CT10166-D1
LLIFE-PRO-CKIT-NP	PCA: Driver Lifelight Pro, Zoneworks Compatible
8002200	PCA: DALI Node

