



CBS4LEDS-DIF-D2

LP Odyssey Quantum 1200MM LED Diffused Batten DALI-2



PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-D2
MIC	AUB0221180001
Description	LP Premium Quantum 1200mm LED Diffused Batten with LED Emergency Pod
Construction	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	DALI-2
Battery	Lithium Iron Phosphate LP 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	LED XZ Driver – 50w 700mA, 30-54V
Lamp(s)	LED Strip Module, 4,000K Natural White, 50,000h Life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	39W (Lamps ON), 0.4W (Lamps OFF, Standby)
Inrush Current (Max)	
Earth Leakage	0.014mA
Total Lumen Output	4585lm @ 115lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8002695	Emergency LED Panel
AUM02270550001 CLIFE-CKIT-D2-NP	Emergency Driver
1330059	240V Driver
8003062	Emergency Node – DALI-2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.