




## CBS4LEDS-DIF-DD-D2

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN, DALI-2



### PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-DD-D2
MIC	AUB02211170001
Description	LP Premium Quantum LED diffused batten with LED Emergency Pod, DALI-2
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	DALI Driver, EEI=A1, 50,000h
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.95
Power Consumption	42 Watts (Lamps ON), 1.0 Watts (Lamps OFF)
Total Lumen Output	4585lm @109lm/W (112lm/W for non-EM version)
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8002695	Emergency LED Panel
1330040	240V Driver
AUM02370170001 CLIFE-CKIT-NP	Emergency Driver
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.