



CBS4LEDS-DIF-DD-HVG

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN
(ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-DD-HVG
MIC	AUB02910120001
Description	LP Premium Odyssey Quantum LED Diffused Batten with LED Emergency Pod and Dali Driver
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	DALI Driver: 50W 350-1050mA
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.95
Power Consumption	44W (Lamps ON Max), 1.3W (Standby)
Inrush Current (Max)	TBC
Earth Leakage	0.144mA
Total Lumen Output	4585lm @ 118lm /W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	N/A
AS2293 Classification	C0=40, C90=40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8002695	240V LED x 2
1100635	EM LED
1330056	240V Driver
AUM02970060001	EM Driver
8003580	Hive Node

as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.