




CBS4LEDS-DIF-MS-HL-D2

Odyssey Diffused 1200mm Emergency Batten, LP, Motion Sensor, DALI-2



PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-MS-HL-D2
MIC	AUB02211230001
Description	Odyssey Diffused 1200mm Emergency Batten, LP, Motion Sensor, DALI-2
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Weight	3.5kg
Operating Mode	Sustained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	40w Stallion
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	1.2W (Standby), 45.7W (MAX)
Power Consumption	42 Watts (Standby Lamp MAX), 8.6 Watts (Standby Lamp MIN)
Total Lumen Output	4585lm @112lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
1330070	240V Driver
8002695 x2	Led Strip
1190118	Microwave Sensor
AUM02270550001 CLIFE-CKIT-D2-NP	Driver Pack
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.