

## Odyssey Diffused 1200mm Emergency Batten, LP, Zoneworks XT Hive 2.4GHz, Low Output



### PRODUCT INFORMATION

Catalogue Number	CBS4LEDS-LO-DIF-HVG
MIC	AUB02910160001
Description	Odyssey Diffused 1200mm Emergency Batten, LP, Zoneworks XT Hive 2.4GHz, Low Output
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	Driver: 21W, 700mA, 220-240V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.95
Total lumen output	2438lm @ 135lm /W
Power Consumption	22.5W (Max charging, Lamp ON), 19W (Standby, Lamp ON), 1.3W (Standby, Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330023	LED Driver - 21W, 700mA, 220-240V
CLIFE-CKIT-HVGEXTA-NP	Lifelight, Control Only, HVG, LP, No Plug (incl. Hive node)
8003580	PCA: V5 2.4GHz RF Node CT10816-A1 Ext Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order