



FBS4LED-DIF-DD

240V Odyssey Quantum LED Diffused Batten with DALI Driver



PRODUCT INFORMATION

Part Number	FBS4LED-DIF-DD
MIC	AUB04610080001
Description	240V Odyssey Quantum LED Diffused Batten with DALI Driver
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	1238mm x 120mm x 110mm
Driver / Ballast	DALI Driver, 50,000h
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], (CRI) Ra>80
Short Term Light Modulation (PstLM)	≤1.0
Stroboscopic Visibility Measure (SVM)	≤0.4
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Inrush Current (Peak/Duration)	35A/170μs
Earth Leakage	0.140mA
Total lumen output	4585 lm @ 118lm/W
Power Consumption	39 Watts
SDCM (MacAdams)	5
IP Rating	IP20
Operating Temperature	1°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330056	240V Driver
8002695	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.