



## FORM-16-SM-WM-LP-ESC

Form 16M Exit, Surface Wall Mount, LP, Clevertest Plus,  
All Pictograms, Single Sided, Brushed Aluminium Frame



PRODUCT INFORMATION	
Product Code	FORM-16-SM-WM-LP-ESC
MIC	AUA02310760001
Description	Form 16M Exit, Surface Wall Mount, LP, Clevertest Plus, All Pictograms, Single Sided, Brushed Aluminium Frame
Construction	PCM Box with PC/Aluminium Extrusion Blade
Diffuser	Polycarbonate
Mounting	Wall Mount, Single Sided
Electrical Connection	Push Terminal
Viewing Distance	16m
Operating Mode	Maintained
Testing System	Clevertest Plus
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)*	18 x LED, >100,000hrs (AS/NZS2293.3 LSL=73Y/00M)
Supply Voltage	220-240V~ 50Hz
Power Factor	0.28 (Standby, Maintained), 0.42 (Max)
Supply Current	19.91 (Standby, Maintained), 35.60 (Max) - (mA)
Inrush Current (Max)	10A<144µs
Earth Leakage	0.35mA
Power Consumption	1.2W (Standby), 3.3W (Max)
Operating Temperature	1 °C - 40°C
IP Rating	IP42
Impact Rating	IK03
Escape Route Illumination	2 x Directional & Rotational Lens
AS2293 Classification	Refer to next page
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking	



## FORM-16-SM-WM-LP-ESC


Form 16M Exit, Surface Wall Mount, LP, Clevertest Plus,  
All Pictograms, Single Sided, Brushed Aluminium Frame

### AS/NZS 2293.1:2018 CLASSIFICATION

Twin Rotating Emergency Lens – Orientation		C0	C90	C180	C270
<b>Perpendicular</b> to the blade		D32	C10	D32	C12.5
<b>Parallel</b> to the blade		C12.5	D32	E5	D32
<b>Mixed</b> one perpendicular, one parallel to the blade)		D25	D20	D20	D25

### DIMENSIONS

Blade Assembly (LxWxH mm)	220 x 18 x 110
Body/Box (LxWxH mm)	210 x 25 x 100
Cover Plate (LxW mm)	N/A
Rod/Cable (LxDIAØ mm)	N/A
Cut-Out (LxW mm)	N/A
Minimum Ceiling Depth (mm)	N/A
Weight (kg)	0.55



### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8011950	LED Strip
AUM02370500001	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications, or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order