



ARGOWALL-LP-D2

Argonaut Wall Light IP65 Weatherproof, Emergency, LP, Maintained, DALI-2 Emergency, Anthracite Grey (RAL7016)



PRODUCT INFORMATION

Part Number	ARGOWALL-LP-D2
MIC	AUS02220410001
Description	Argonaut Wall Light IP65 Weatherproof, Emergency, LP, Maintained, DALI-2 Emergency, Anthracite Grey (RAL7016)
Construction	Die Cast Aluminium Body with Polycarbonate LED Cover
Mounting	Surface Mount (Wall, with LED light source facing downwards)
Dimensions	305mm (W) x 310mm (H) x 155mm (D)
Weight	4.6kg
Operating Mode	Maintained (with integrated photocell for automatic on/off operation Depending on ambient light levels)
Testing System	DALI-2
Battery	Lithium Iron Phosphate 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, 4000K, 100,000h [L70/ B50, Ta 40°C], Ra>80
Diffuser	Polycarbonate with asymmetric lenses over the LEDs to suit wall mounted, walkway, applications (LED cover fitted with 4 security torx head screws)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	19.9W (Lamps ON Max Charge), 15.8W (Lamps ON Standby), 1.4W (Lamps OFF Standby)
Power factor	0.9
Supply Current	111mA (Lamps ON Max Charge), 89mA (Lamps ON Standby)
Inrush Current (Peak/Duration)	6.96A/16.8µS
Earth Leakage	
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
AS2293 Classification	C0=D40, C90=D125, C180=D50, C270=D125
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	Battery
1330153	LED Driver – TCI PRO FLAT 30 BI
AUM02270730001 CCPLED-WP-5W-CKIT-D2	EM Driver
8050219	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.