



CCFPRO-BLK

CLEVERTRONICS LP Cleverfit PRO Exit, Black



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | CCFPRO-BLK |
| MIC | AUA02310060001 |
| Description | LP Premium Cleverfit PRO Emergency Exit, Black |
| Construction | Fire-retardant PC/ABS Body with Polycarbonate Diffuser |
| Mounting | Wall, Ceiling Single-Sided & Ceiling Double-Sided |
| Dimensions L x W x H | 367mm x 72mm x 214mm |
| Weight | 2.5kg |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Iron Phosphate, 3.2V 1100mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x Duris E2 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8 Watts (Standby), 3.9 Watts (Max) |
| Inrush Current (Max) | 12.851A |
| Earth Leakage | 0.321mA |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=D3.2, C90=E4 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1550105 | Battery |
| 8002710 | LED Strip |
| 8003090 | Driver |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.