

## CLEVERTRONICS L10 CLEVERFIT PRO THEATRE EXIT (DALI)



### PRODUCT INFORMATION

Part Number	LCFPRO-TH-DALI-R
MIC	AUA01260470002
Description	L10 Optimum Cleverfit PRO Theatre Emergency Exit
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall and ceiling single-sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask with Running Man (Must specify diffuser combination)
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 3.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A - Theatre Mask
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002920	PCA:CCF-Pro #CT10142-L8 CTP
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8003060	PCA: DALI Node #CT10629-Ax

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*