



LCFPRO-TH-HV-R

CLEVERTRONICS L10 CLEVERFIT PRO EXIT THEATRE



PRODUCT INFORMATION	
Part Number	LCFPRO-TH-HV-R
MIC	AUA01860010001
Description	L10 Premium Cleverfit Pro Emergency Exit, Theatre Mask
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, ceiling single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Cut-Out	N/A
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh/
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask Running man (Must specify diffuser combination)
Lamp(s)	6 x LED, 100,000
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby) 3.4 Watts (Max)
Inrush Current (Max)	13A, 82uS
Earth Leakage	0.339mA
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A, C90=N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002710	LED Strip
8003191	RF Node Hive
8003156	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.