




LCFPRO

Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus,
All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LCFPRO
MIC	AUA01310040001
Description	Cleverfit Pro Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided, supports 4-Hour Emergency Duration
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E2 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8W (Standby), 3.9W (Max)
Inrush Current (Max)	13.4A
Earth Leakage	0.305mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D3.2 C90=B16
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8003090	Driver
8002710	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.