

CLEVERTRONICS L10 CLEVERFIT PRO EXIT



PRODUCT INFORMATION

Part Number	LCFPRO-BLK
MIC	AUA01310150001
Description	L10 Optimum Cleverfit PRO Emergency Exit, Enabled with Clevertest Plus, Black
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E2 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D3.2 C ₉₀ =B16
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8003090	PCA: Cleverfit Narrow #CT10622-Lx
8002720	PCA:Test Sw/ LED CPRO gen2 CT10274-A2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order