



## CCFPRO CLEVERTRONICS LP CLEVERFIT PRO EXIT



PRODUCT INFORMATION	
Part Number	CCFPRO
MIC	AUA02310010003
Description	LP Premium Cleverfit PRO Emergency Exit, Enabled with Clevertest Plus
Construction	Fire-retardant PC/ABS Body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D3.2 C90=E4
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT.
8003090	PCA: Cleverfit Narrow #CT10622-Lx
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.